

# Addvent In-Line Shower Fan



## Product Description

In-Line Axial Shower Fan Range

### Key Features

- Safe, Remote Mounting
- AVX100 23 litres/sec (85m<sup>3</sup>/hr)
- AVX150 64 litres/sec (230m<sup>3</sup>/hr)
- Quiet yet powerful
- Suitable for in-duct mounting only


### Technical Details

|                          |  |
|--------------------------|--|
| <b>Construction</b>      | Impact resistant ABS thermoplastic;  |
| <b>Rating</b>            | 220-240V ~50Hz~AC 20W 100mm, 25W 150mm   |
| <b>IP Rating</b>         | <b>IP24</b>  |
| <b>Class</b>             | Double Insulated   |
| <b>MOTOR:</b>            | Single-phase induction motor with pre-oiled bearings; All with thermal overload protection |
|                          | Maximum operating Temperature 40°C   |
| <b>Approvals</b>         | BEAB, CE   |
| <b>Warranty</b>          | 5 Years Exchange   |
| <b>Country of Origin</b> | UK   |
| <b>Manufacturer</b>      | Addvent  |

### Models

| Model No.   | Product Description                         |
|-------------|---|
| AVX100IDS   | 100mm Axial In-duct Standard Fan Kit        |
| AVX100IDT   | As Above with overrun timer 1 to 20 minutes |
| AVX100IDFT  | 100 mm In-Line Fan Only with Overrun timer  |
| AVX150IDFT  | 150mm Axial In-duct timer fan kit           |
| AVX150IDFTR | 150mm Axial In-duct Timer Fan Only          |

### Dimensions



| Size | ØA  | B   | C  |
|------|-----|-----|----|
| 100  | 100 | 90  | 27 |
| 150  | 150 | 109 | 27 |

### Performance Details

| Induct Range | m <sup>3</sup> /hr | l/s | dB(A) @ 3m | Power (W) | Max (pa) |
|--------------|--------------------|-----|------------|-----------|----------|
| 100mm        | 85                 | 23  | 41         | 20        | 20       |
| 150mm        | 230                | 64  | 40         | 25        | 50       |

