



Product Description

In-Line Axial Shower Fan Range

Key Features

- Safe, Remote Mounting
- AVX100 23 litres/sec (85m³/hr)
- AVX150 64 litres/sec (230m³/hr)
- Quiet yet powerful
- Suitable for in-duct mounting only




Technical Details				
Construction	Impact resistant ABS thermoplastic;			
Rating	220-240V ~50Hz~AC 20W 100mm, 25W 150mm			
IP Rating	IP24			
Class	Double Insulated			
MOTOR:	Single-phase induction motor with pre-oiled bearings; All with thermal overload protection			
	Maximum operating Temperature 40°C			
Approvals	BEAB, CE			
Warranty	5 Years Exchange			
Country of Origin	UK			
Manufacturer	Addvent			

Performance Details


Induct Range	m³/hr	I/s	dB(A) @ 3m	Power (W)	Max (pa)
100mm	85	23	41	20	20

Models			
Model No. Product Description			
AVX100LEDSLC	LED In-Duct Shower light with overrun timer -		
	Warm White Lamp		
AVX100LEDCW	LED In-Duct Shower light with overrun timer -		
	Warm White Lamp		

Dimensions



Size	ØA	В	C
100	100	90	27



Size	A	В	С	Hole Size (mm)
100	140	98	74	102

Installation

AVX100IDTSLCN/B shower light fan is supplied complete with a 1.5m length of flexible PVC ducting

Designed to be ceiling mountedthrough 102mm Diameter flexible ducting or rigid pipes

Electrical

12 volt DC 3W MR16 Lamp